

DECLARATION of PERFORMANCE (DoP)

No. SafeLine-R (H2) – T522

Manufacturer	Vik Ørsta AS Box 193, N-6151 Ørsta, Norway Telephone: +47 70 04 70 00	Web: www.Vikorsta.no
Product identification code	SafeLine-R – safety barrier c/c 2 m	
Product type	SafeLine-R H2-W5-CC2	
Intended use	In vehicle circulation areas / roads	
Harmonized standard	EN 1317-5:2007 / A2:2012	
System of assessment and verification	System 1 (CPR no. 305/2011)	
Name of notified body	RISE Research Institute of Sweden	
Identification number of the notified body	No. 0402	
Description of the notified body tasks	Performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control	
EC Certificate of Conformity	No. 0402 – CPR - SC0212-19	

Declared performance

Essential characteristics	Performance	Harmonized standard
Performance under impact: - containment level - impact severity - working width - dynamic deflection - vehicle intrusion	H2 A 1,6 m (W5) 1,5 m 1,9 m (VI6)	EN 1317-5:2007 / A2:2012 EN 1317-5:2007 / A2:2012 EN 1317-5:2007 / A2:2012 EN 1317-5:2007 / A2:2012 EN 1317-5:2007 / A2:2012
Resistance to snow removal:	Class 4	EN 1317-5:2007 / A2:2012
Durability: - of performance under impact - of resistance to snow removal	Hot dip galvanized coatings according to NS-EN ISO 1461 and Statens Vegvesen handbook N101	EN 1317-5:2007 / A2:2012 EN 1317-5:2007 / A2:2012

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of
the manufacturer by:

John H. Systad
-Product manager-



Vik i Sogn 2019-11-29