

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Road restraint systems - Part 5: Product requirements and evaluation of conformity for vehicle restraint systems

Safety barriers for use in vehicle restraint system in circulation areas, with specification and performance as specified on page 2 in this certificate.

Product name: SafeLine-R

placed on the market under the name or trademark of

VIK Ørsta AS

Postboks 193
NO-6150 Ørsta, Norway

and produced in the manufacturing plants

VV, VO, 30004, 30077, 30092, 31222, 31548, 32816 and 32964

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standards

EN 1317-5:2007+A2:2012 and EN 1317-5:2007+A2:2012/AC:2012

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 2019-07-05 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Issued by notified body 0402

The validity of this certificate can be verified on our website.

Martin Tillander
Director Product Certification

Certificate 0402-CPR- SC0212-19 | issue 2 | 2020-05-11

RISE Research Institutes of Sweden AB | Certification

Box 857, SE-50115 Borås, Sweden

+46 10 516 50 00 | certifiering@ri.se | www.ri.se

2P01042

This document is the property of RISE and may not be reproduced other than in full, except with the prior written approval by RISE



Specification

Product	Description and configuration
SafeLine-R N2-W3-cc4 SafeLine-R N2-W4-cc6	Post distance: 4.0 m or 6.0 m Height from road surface: 0.76 m (total), 0.46 m (centre of lower rail) Rails: Top- and lower rail: Ø 88.9, thickness 2.9 mm Material: S355 Steel post: C 100 × 60 × 25 mm, thickness 4 mm Length min 1.545 m, driven in soil min 0.80 m, for baseplate 0.696 m Material: S355 BasePlate: Plate 200 × 200 × 20 mm (thickness of 20 mm is a minimum) Steel S355 Steel tape 44 × 3 mm Steel S235J
SafeLine R H2-W5-cc2	Post distance: 2.0 m Height above road surface: 0.85 m (total), 0.55 m (centre of lower rail) Steel rail: Top- and lower rail: Ø 88.9, thickness 3.6 mm Material: S355 Steel post: C 100 × 60 × 25 mm, thickness 4 mm Length min 1.715 m, driven in soil min 0.88 m Material: S355 BasePlate: Plate 200 × 200 × 20 mm (thickness of 20 mm is a minimum) Steel S355 Steel tape 44 × 3 mm Steel S235J

Performance

Classification according to EN 1317-5:2007+A2:2012/AC:2012 (EN 1317-2:2010)

Product	Containment level	Impact severity level	Normalized working width, class [m]	Normalized dynamic deflection, [m]	Normalized Vehicle intrusion, class [m]
SafeLine-R N2-W3-cc4	N2	A	W3 (1.0)	0.9	NA
SafeLine-R N2-W3-cc4 with baseplate	N2	A	W3 (1.0)	1.0	NA
SafeLine-R N2-W4-cc6	N2	A	W4 (1.3)	1.1	NA
SafeLine-R N2-W4-cc6 with baseplate	N2	A	W4 (1.3)	1.3	NA
SafeLine R H2-W5-cc2	H2	A	W5 (1.6)	1.5	VI6 (1.9)
SafeLine R H2-W5-cc2 with baseplate	H2	A	W5 (1.7)	1.6	VI6 (1.9)

Classification according to EN 1317-5:2007+A2:2012/AC:2012 (EN 1317-2:2010)

Product	Durability	Resistance to snow removal class
SafeLine-R	Hot dip galvanized, acc. To EN ISO 1461	Class 4